



Moduły do podświetleń tylnych

Modules for back lighting • Flächenbeleuchtung • Модули для задней подсветки

Barwa światła • Colour temp. • Farbtemperatur • Цветовая температура



	GEM-X • GEM-X CC		RX-2 Stark	RX-3 Stark	RX-2E Stark	RX-3E Stark	Ultra-Board	Flex-Board	Back-Board	BS-1 XL Max	BS-2 XL Max	BS-3 XL Max	BS-3 XL	BS-2 Eco	BS-3 Eco	LS-3 XL	LS-3	XR-1	XR-1 HP	XR-4 CC	XR-4	ML-1 • ML-1 Plus	SV-1 Back	AS-2	MN-1 MN-2 MN-3	AXS-1	AXS-2	AXS-3	SV-3	
Cena Netto Net price Nettopreis цена нетто																														
Model Modell Модель	GEM-X • GEM-X CC	RX-2 Stark	RX-3 Stark	RX-2E Stark	RX-3E Stark	Ultra-Board	Flex-Board	Back-Board	BS-1 XL Max	BS-2 XL Max	BS-3 XL Max	BS-3 XL	BS-2 Eco	BS-3 Eco	LS-3 XL	LS-3	XR-1	XR-1 HP	XR-4 CC	XR-4	ML-1 • ML-1 Plus	SV-1 Back	AS-2	MN-1 MN-2 MN-3	AXS-1	AXS-2	AXS-3	SV-3		
Moc Leistung Мощность	1.2 W	0.48 W	0.72-1.20 W	0.48 W	0.72 W	5.88-10.92 W	16-32 W	3 W	0.45 W	0.9 W	1.4 W	1.2 W	0.48 W	0.72 W	1.5 W	0.72 W	0.72 W	1.2-1.5 W	4-6 W	4-6 W	0.36 W	0.20 W	0.32 W	0.1-0.32 W	0.24 W	0.48 W	0.72 W	0.30 W		
Napięcie Voltage Spannung Напряжение	12 V	12 V	12 V	12 V	12 V	12 V	12 V	24 V	12 V	12 V	12 V	12 V	12 V	12 V	12 V	12 V	12 V	12 V	12 V	12 V	12 V	12 V	12 V	12 V	12 V	12 V	12 V	12 V	12 V	
Typ LED LED type LED-Typ Тип светодиода	2835 SMD Samsung	2835 SMD Samsung • 5050 SMD	2835 SMD Samsung • 5050 SMD Itswell	2835 SMD Itswell	2835 SMD Itswell	3030 SMD	2835 SMD	3030 SMD Philips	2835 SMD	2835 SMD	2835 SMD	2835 SMD Epistar	2835 SMD	2835 SMD	2835 SMD	2835 SMD	2835 SMD	3030 SMD OSRAM • 3030 SMD Epistar	3030 SMD	3030 SMD	2835 SMD	2835 SMD	2835 SMD • 3528 SMD	3528 SMD • 4014 SMD	2835 SMD	2835 SMD	2835 SMD	2835 SMD + 2 x 3014 SMD		
Strumień świetlny Luminous flux Lichtstärke Световой поток	119 lm	44 lm	77-121 lm	42 lm	72 lm	640-1250 lm	1740-3480 lm	390 lm	67.5 lm	135 lm	210 lm	110-115 lm	44 lm	70 lm	145 lm	70 lm	70 lm	120 lm	390-580 lm	390-580 lm	36-41 lm	20 lm	18-20 lm	4-40 lm	25 lm	50 lm	80 lm	30 lm		
Kąt świecenia Beam angle Abstrahlwinkel Угол рассеивания	160°	160°	160°	160°	160°	180°	175°	160°	165°	170°	170°	160°	160°	160°	160°	160°	170°	180°	170°	170°	170°	170° x 130°	120°	120°	120°	183° x 142°	183° x 142°	183° x 142°	180° x 120°	
Barwa światła Colour temp. Farbtemperatur Цветовая температура																														
Maks. szt./łańcuch Max pcs/chain Max. Kettenlänge Макс. кол. мод./цепь	50	50	50	50	50	9-14	-	10	20	20	20	20	20	20	20	20	50	20	20	20	20	50	100	50	30	40	40	40	x 165	
IP	IP66	IP68	IP68	IP68	IP68	IP20	IP20	IP65	IP67	IP67	IP67	IP65	IP67	IP67	IP65	IP65	IP65	IP65	IP65	IP65	IP65	IP67	IP67	IP65	IP65	IP67	IP67	IP67	IP67	IP20
Gwarancja [lata] Warranty [years] Die Garantiezeit [Jahre] Гарантия [лет]	7	5	5	5	5	5	3	3	5	5	5	4	≥ 3	≥ 3	≥ 3	≥ 3	5	5	5	3	5	5	≥ 3	2	5	5	5	5	2	
Sugerowana gł. kasetonu Suggested lightbox depth Empfohlene Bauhöhe Предпочтительно исп. в лайтбоксах	60-170 mm	40-100 mm	60-170 mm	40-100 mm	60-150 mm	40-100 mm	40-100 mm	60-150 mm	40-80 mm	60-170 mm	60-150 mm	80-150 mm	50-100 mm	80-150 mm	80-150 mm	60-120 mm	35-120 mm	40-150 mm	>140 mm	>140 mm	30-50 mm	30-100 mm	30-50 mm	30-50 mm	20-60 mm	30-100 mm	40-100 mm	40-100 mm		
Wymiary [LxWxH] Dimensions [LxWxH] Maße [LxWxH] Размер [LxWxH]	84 x 19 x 12 mm	43 x 15 x 10 mm	68 x 15 x 8.1 mm	43 x 15 x 10 mm	68 x 15 x 8.1 mm	480 x 16 x 7 mm (16 W) • 930 x 16 x 7 mm (32 W)	503.5 x 235 x 5.5 mm	250 x 24 x 8 mm	25.5 x 10.5 x 8.5 mm	55.5 x 15.5 x 9.5 mm	80.5 x 15.5 x 9.5 mm	77 x 15.9 x 7.8 mm	56 x 19 x 6.5 mm	74 x 17 x 5.8 mm	83 x 15 x 7.2 mm	74 x 15 x 8.6 mm	37 x 25.5 x 7 mm	51 x 32 x 9 mm	61 x 66 x 7.5 mm	61 x 66 x 7.5 mm	16 x 8.5 x 8 mm	9 x 6.8 x 4.8 mm	30 x 9 x 4.3 mm	12 x 4 x 3.5 mm (MN-1) • 20 x 5 x 3.5 mm (MN-2) • 40 x 5 x 3.5 mm (MN-3)	14.1 x 9.1 x 9.8 mm	26 x 9 x 9.8 mm	38 x 9 x 9.8 mm	14 x 8.64 x 2.6 mm		